



Ø	0080	0100	0115	0120	0130	0140	0150	0160	0180	0200	0225	0250	0300	0350	0400	0450	0500	0550	0600
<b>B</b>	195	215	230	235	245	255	265	275	295	315	340	365	415	465	515	565	615	665	715
<b>C</b>	230	250	265	270	280	290	300	310	330	350	375	400	450	500	550	600	650	700	750
<b>E</b>	665	690	705	710	725	735	745	760	780	805	835	860	920	975	1035	1095	1150	1210	1265
<b>F</b>	630	650	665	670	680	690	700	710	730	750	775	800	850	900	950	1000	1050	1100	1150
<b>kg</b>	2,8	3	3,1	3,2	3,3	3,4	3,5	3,7	3,8	4,1	4,3	4,6	5,2	5,8	6,5	7,1	7,8	8,5	9,2

notes:	DIN ISO 13920 Tolerances B			 <b>Jeremias</b> <sup>®</sup> CHIMNEY SYSTEMS	scale
	revisions-no.				1:12
	date	name			format
	drawn by	JMA			A4
	checked by	SWA			sheet
	approved by	JWY			1 of 1
modified by	description				
	Flashing kit 26-35°, incl. storm collar				
	code			DWECO39	
	drawing-no.			02-35-5305-000	

© Jeremias GmbH. All rights reserved, also regarding any disposal, exploitation, editing, distribution, as well as in the event of applications for industrial property rights.